

- **Model:** HXLBQ-DTA229
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2496~2690MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	2593MHz
● Pass Band Frequency	2496 ~ 2690MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Return Loss	≤18dB
● Stop Band Rejection	≥65dB @ DC ~ 2300MHz      ≥40dB @ 2886 ~ 4000MHz
● Impedance	50 Ohms
● Power	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: H59 Copper, Plated ternary alloy
  - Other screw: Stainless Steel
  - Dimensions: 92\*92\*33mm

