

- **Model:** HXLBQ-DTA163
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1345~1385MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	1365MHz
● Pass Band Frequency	1345 ~ 1385MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥50dB @ F0±120MHz (DC ~ 1245MHz , 1485 ~ 3000MHz)
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	N-Male / N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 98*42*20mm |

