

- **Model:** HXLBQ-DTA392
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1920~1980MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1950MHz
● Pass Band Frequency	1920 ~ 1980MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.6dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥50dB @ F0±70MHz (DC ~ 1880MHz , 2020 ~ 5500MHz)
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 98*50*38mm |

