

- **Model:** HXLBQ-DTA178
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 869~880MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	874.5MHz
● Pass Band Frequency	869 ~ 880MHz
● Pass Band Insertion Loss	≤2.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥20dB @ DC ~ 864MHz      ≥20dB @ 885 ~ 1600MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: H59 Copper, Plated ternary alloy
  - Other screw: Stainless Steel
  - Dimensions: 95\*65\*48mm

