

- **Model:** HXLBQ-DTA180
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 980~1020MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	1000MHz
● Pass Band Bandwidth	40MHz (980 ~ 1020MHz)
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥45dB @ Fc±30MHz (DC ~ 950MHz , 1050 ~ 2500MHz)
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.34KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: H59 Copper, Plated ternary alloy
 - Other screw: Stainless Steel
 - Dimensions: 169*57*30mm

