

- **Model: HXLBQ-DTA213**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1350~1450MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	1400MHz
● Pass Band Frequency	1350 ~ 1450MHz
● Pass Band Insertion Loss	≤0.6dB @ 1390 ~ 1410MHz ≤1.0dB @ 1350 ~ 1450MHz
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥50dB @ DC ~ 1278MHz ≥50dB @ 1559 ~ 3000MHz
● Impedance	50 Ohms
● Power Handling	20W Max
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 152*56*25mm |

