

- **Model:** HXLBQ-DTA225
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 9320~9420MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	9370MHz
● Pass Band Frequency	9320 ~ 9420MHz
● Pass Band Insertion Loss	≤2.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥70dB @ DC ~ 9170MHz ≥70dB @ 9570 ~ 18000MHz
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: H62 Copper alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: H62 Copper alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 90*17*12mm |

