

- **Model:** HXLBQ-DTA252
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1280~1380MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	1330MHz
● Pass Band Frequency	1280 ~ 1380MHz
● Pass Band Insertion Loss	≤0.8dB
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥60dB @ DC ~ 1130MHz ≥60dB @ 1470 ~ 3500MHz
● Impedance	50 Ohms
● Power Handling	50W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 180*50*30mm |

