

- **Model:** HXLBQ-DTA259
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 730~750MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	740MHz
● Pass Band Frequency	730 ~ 750MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥40dB @ DC ~ 720MHz ≥40dB @ 760 ~ 2000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.55KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: H59 Copper, Plated ternary alloy
 - Other screw: Stainless Steel
 - Dimensions: 148*76*49mm

