

- **Model:** HXLBQ-DTA436
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 703~743MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	723MHz
● Pass Band Frequency	703 ~ 743MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.7dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥50dB @ DC ~ 688MHz ≥50dB @ 758 ~ 2000MHz
● Impedance	50 Ohms
● Power	50W Max.
● Connectors	N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: H59 Copper, Plated ternary alloy
 - Other screw: Stainless Steel
 - Dimensions: 239*70*30mm

