

- **Model: HXLBQ-DTA292**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2250~2300MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	2275MHz
● Pass Band Frequency	2250 ~ 2300MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥50dB @ DC ~ 2225MHz      ≥50dB @ 2325 ~ 5000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: Stainless Steel
  - Other screw: Stainless Steel
  - Dimensions: 120\*62\*33mm

