

- **Model:** HXLBQ-DTA317
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 12~13GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	12.5GHz
● Pass Band Frequency	12 ~ 13GHz
● Pass Band Insertion Loss	≤0.6dB
● Pass Band Ripple	≤0.2dB
● Pass Band VSWR	≤1.22:1
● Stop Band Attenuation	≥50dB @ DC ~ 11GHz ≥50dB @ 14 ~ 30GHz
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.06 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: H62 Copper alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: H62 Copper alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 70*16*11mm |

