

- **Model:** HXLBQ-DTA370X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1410~1430MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	1420MHz
● Pass Band Frequency	1410 ~ 1430MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.6dB
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥60dB @ DC ~ 1380MHz      ≥60dB @ 1460 ~ 3500MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	N-Male / N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Dimensions	95*65*31mm
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
  - Housing: Aluminum alloy
  - Cover: Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Resonant column: H59 Copper alloy
  - Connectors: H59 Copper, Plated ternary alloy
  - Other screw: Stainless Steel

