- **Model：HXLBQ-DTA424**
- **Product Name：Interdigital Band Pass Filter**
- **Frequency：950~1450MHz**

★High Stop Band Rejection
★Low Pass Band Insertion Loss
★Customizable Design
★High Reliability

Technical Data Sheet		
Item	**Parameters**	
● Center Frequency(F0)	1200MHz	
● Pass Band Bandwidth	500MHz (950 ~ 1450MHz)	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band VSWR	≤1.5:1	
● Stop Band Rejection	≥35dB @ DC ~ 850MHz	≥35dB @ 1550 ~ 2500MHz
● Impedance	50 Ohms	
● Power Handling	2W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30℃ ~ +70℃	
● Net weight	TBD	

Note：The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

●Material	●Housing: 6061 Aluminum alloy	●Connectors: Stainless Steel
	●Cover: LY12 Aluminum alloy	●Other screw: Stainless Steel
	●Tuning screw: H62 Copper alloy	●Dimensions: 93*72*11mm



Tel:+86-029-85450833 FAX:+86-029-85450833 E-mail:sales_hxwb@163.com E-mail: sales@xahxmicrowave.com
http://www.xahxmicrowave.com http://www.hx-microwave.com Add:Yanta District, Xi'an, China