

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA843LC
- **Frequency:** 1395~1405MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1400MHz
● Pass Band Bandwidth	10MHz (1395 ~ 1405MHz)
● Pass Band Insertion Loss	≤3.5dB
● Pass Band Ripple	≤0.3dB
● Pass Band VSWR	≤1.4:1
● Stop Band Rejection	≥25dB @ DC ~ 1300MHz ≥25dB @ 1500 ~ 3000MHz
● Impedance	50 Ohms
● Power Handling	1.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.025 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|--------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Dimensions: 40*18*13mm |

