

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA750LC
- **Frequency:** 566~678MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency	622MHz
● Pass Band Frequency	566 ~ 678MHz
● Pass Band Insertion Loss	≤1.8dB
● Pass Band Ripple	≤0.5dB
● Pass Band Return Loss	≥14dB
● Stop Band Rejection	≥50dB @ DC ~ 455MHz ≥50dB @ 840 ~ 1500MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|--------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Dimensions: 60*24*15mm |

