

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA776LC
- **Frequency:** 170~230MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	200MHz
● Pass Band Frequency	170 ~ 230MHz
● Pass Band Insertion Loss	≤1.4dB
● Pass Band Ripple	≤0.6dB
● Pass Band VSWR	≤1.4:1
● Stop Band Rejection	≥40dB @ DC ~ 130MHz      ≥40dB @ 270 ~ 800MHz
● Impedance	50 Ohms
● Power Handling	1.0W Max.
● Connectors	SMA-Male / SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.025 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- |                   |                                |                               |
|-------------------|--------------------------------|-------------------------------|
| ◆ <b>Material</b> | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy   | ● Dimensions: 40*18*13mm      |

