

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA279LC
- **Frequency:** 95~105MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	100MHz
● 1.0dB Pass Band Bandwidth	10MHz (95 ~ 105MHz)
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥60dB @ DC ~ 60MHz      ≥60dB @ 145 ~ 300MHz
● Impedance	50 Ohms
● Power Handling	1.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- ◆ **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
- Connectors: H59 Copper, Plated ternary alloy
  - Dimensions: 40\*18\*13mm

