

- **Model:** HXLBQ-DTA492
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 4000~4050MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	4025MHz
● Pass Band Frequency	4000 ~ 4050MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.2dB
● Pass Band Return Loss	≥20dB
● Stop Band Attenuation	≥80dB @ DC ~ 3890MHz ≥40dB @ 4100 ~ 4160MHz ≥40dB @ 3890 ~ 3950MHz ≥80dB @ 4160 ~ 9000MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: Stainless Steel
 - Working Environment: Indoor
 - Dimensions: 110*21*20mm

