

- **Model:** HXLBQ-DTA568
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1410~1420MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1415MHz
● Pass Band Frequency	1410 ~ 1420MHz
● Pass Band Insertion Loss	≤0.6dB
● Pass Band Ripple	≤0.2dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥30dB @ DC ~ 1385MHz      ≥30dB @ 1445 ~ 3500MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: Stainless Steel
  - Working Environment: Indoor
  - Dimensions: 93\*93\*44mm

