

- **Model: HXLBQ-DTA575**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1475~1525MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1500MHz
● Pass Band Frequency	1475 ~ 1525MHz
● Pass Band Insertion Loss	≤1.2dB
● Pass Band Ripple	≤0.5dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥40dB @ DC ~ 1455MHz      ≥40dB @ 1545 ~ 3500MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ● <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy     | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 120*62*38mm     |

