

- **Model:** HXLBQ-DTA649
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2412~2484MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2448MHz	
● Pass Band Frequency	2412 ~ 2484MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥60dB @ DC ~ 2382MHz	≥60dB @ 2514 ~ 5500MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Net weight	0.285 KG	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 120*62*33mm |

