

- **Model:** HXLBQ-DTA650
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 4915~5825MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters	
● Center Frequency(F0)	5370MHz	
● Pass Band Frequency	4915 ~ 5825MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 4750MHz ≥60dB @ 4750 ~ 4795MHz	≥60dB @ 5945 ~ 5980MHz ≥80dB @ 5980 ~ 17000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Net weight	TBD	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ● <b>Material</b> | ● Housing: H62 Copper alloy      | ● Connectors: Stainless Steel |
|                   | ● Cover: H62 Copper alloy        | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 170*18*15mm     |

