

- **Model:** HXLBQ-DTA666
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 12000~13600MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	12800MHz
● Pass Band Frequency	12000 ~ 13600MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.35dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥80dB @ DC ~ 11200MHz ≥80dB @ 14400 ~ 27000MHz
● Impedance	50 Ohms
● Power Handling	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.09 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ● Material | ● Housing: H62 Copper alloy | ● Connectors: Stainless Steel |
| | ● Cover: H62 Copper alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 80*16*13mm |

