

- **Model:** HXLBQ-DTA674
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1250~1385MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1317.5MHz	
● Pass Band Frequency	1250 ~ 1385MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.58dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 1160MHz	≥40dB @ 1425 ~ 1460MHz
	≥40dB @ 1160 ~ 1210MHz	≥80dB @ 1460 ~ 6000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30℃ ~ +70℃	
● Net weight	TBD	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 140*25*31mm |

