

- **Model: HXLBQ-DTA728**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 606~626MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	616MHz
● Pass Band Frequency	606 ~ 626MHz
● Pass Band Insertion Loss	≤1.2dB
● Pass Band Ripple	≤0.4dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥65dB @ DC ~ 576MHz ≥65dB @ 656 ~ 2000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	TNC-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 180*67*30mm |

