

- **Model:** HXLBQ-DTA989
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 7200~7300MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	7250MHz
● Pass Band Frequency	7200 ~ 7300MHz
● Pass Band Insertion Loss	≤1.2dB
● Pass Band Ripple	≤0.15dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥80dB @ DC ~ 6850MHz      ≥50dB @ 7500 ~ 7650MHz ≥50dB @ 6850 ~ 7000MHz      ≥80dB @ 7650 ~ 25000MHz
● Impedance	50 Ohms
● Power Handling	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- ◆ **Material**
  - Housing: H62 Copper alloy
  - Cover: H62 Copper alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: Stainless Steel
  - Working Environment: Indoor
  - Dimensions: 70\*16\*12mm

