

- **Model: HXLBQ-DTA992**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1785~1815MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	1800MHz
● Pass Band Frequency	1785 ~ 1815MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.8dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥60dB @ DC ~ 1740MHz ≥60dB @ 1860 ~ 5000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.252 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: Stainless Steel
 - Other screw: Stainless Steel
 - Dimensions: 100*68*33mm

