



- **Model: HXLBQ-DTA1009**
- **Product Name: Interdigital Band Pass Filter**
- **Frequency: 5000~13000MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	9000MHz
● Pass Band Frequency	5000 ~ 13000MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.6dB
● Pass Band Return Loss	≥11dB
● Stop Band Rejection	≥40dB @ DC ~ 4000MHz ≥30dB @ 14000 ~ 15500MHz
● Impedance	50 Ohms
● Power Handling	2.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: H62 Copper alloy | ● Connectors: Stainless Steel |
| | ● Cover: H62 Copper alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 78*24*12.5mm |

