

- **Model:** HXLBQ-DTA1036
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2440~2460MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	2450MHz
● Pass Band Frequency	2440 ~ 2460MHz
● Pass Band Insertion Loss	≤1.4dB
● Pass Band Ripple	≤0.3dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥40dB @ DC ~ 2410MHz ≥40dB @ 2490 ~ 5000MHz
● Impedance	50 Ohms
● Power Handling	200W Max.
● Connectors	N-Male / N-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: H62 Copper alloy | ● Connectors: Stainless Steel |
| | ● Cover: H62 Copper alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 150*39*25mm |

