

- **Model:** HXLBQ-DZA299
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 5450~5700MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	5450 ~ 5700MHz
● Stop Band Attenuation	≥40dB
● Pass Band Frequency	DC ~ 5320MHz , 5820 ~ 11000MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.7:1
● Impedance	50 Ohms
● Power Handling	30W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-10°C ~ +50°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 137*34*11mm |

