

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA1273LC
- **Frequency:** 190~210MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	200MHz	
● Pass Band Bandwidth	20MHz (190 ~ 210MHz)	
● Pass Band Insertion Loss	≤4.0dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band VSWR	≤1.5:1	
● Stop Band Attenuation	≥40dB @ DC ~ 150MHz	≥40dB @ 250 ~ 6000MHz
● Impedance	50 Ohms	
● Power Handling	1.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Dimensions	50*18*13mm	
● Net weight	0.03 KG	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|--------------------------------|--------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |

