

- **Model:** HXLBQ-DTA1424
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 23~26GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	24.5GHz	
● Pass Band Frequency	23 ~ 26GHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.4dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥80dB @ DC ~ 21.05GHz	≥80dB @ 27.95 ~ 44GHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	2.92mm(K)-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Net weight	TBD	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|------------------------------|-------------------------------|
| ◆ Material | ● Housing: Copper alloy | ● Connectors: Stainless Steel |
| | ● Cover: Copper alloy | ● Working Environment: Indoor |
| | ● Tuning screw: Copper alloy | ● Dimensions: 60*16*11mm |

