

- **Model:** HXLBQ-DTA1430
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 352~358MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	355MHz	
● Pass Band Frequency	352 ~ 358MHz	
● Pass Band Insertion Loss	≤2.5dB	
● Pass Band Ripple	≤1.5dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥40dB @ DC ~ 348MHz	≥40dB @ 362 ~ 800MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	+10°C ~ +50°C	
● Net weight	TBD	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|------------------------------|-------------------------------|
| ◆ Material | ● Housing: Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: Copper alloy | ● Dimensions: 181*93*77mm |

